

AD A139 586

USE OF THE COMPUTER PROGRAM PARA 80 TO STUDY RESULTS  
FROM FIRING THE RAILGUN ERGS-1M(U) MATERIALS RESEARCH  
LABS ASCOT VALE (AUSTRALIA) D D RICHARDSON ET AL.  
AUG 83 MRL-R-900


1/1

UNCLASSIFIED

F/G 19/6

NL

END  
FBI  
4-10-1  
11



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

MRL-R-900

12 AR-003-793



AD A139586

**DEPARTMENT OF DEFENCE**  
**DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION**  
**MATERIALS RESEARCH LABORATORIES**  
**MELBOURNE, VICTORIA**

**REPORT**


**MRL-R-900**

**USE OF THE COMPUTER PROGRAM PARA 80 TO STUDY  
RESULTS FROM FIRING THE RAILGUN ERGS-1M**

**D.D. Richardson & R.A. Marshall**


THE UNITED STATES NATIONAL  
TECHNICAL INFORMATION SERVICE  
IS AUTHORISED TO  
REPRODUCE AND SELL THIS REPORT

Approved for Public Release



DTIC FILE COPY

84 08 29 101



**DEPARTMENT OF DEFENCE  
MATERIALS RESEARCH LABORATORIES**

**REPORT**

**MRL-R-900**

**USE OF THE COMPUTER PROGRAM PARA 80 TO  
STUDY RESULTS FROM FIRING THE RAILGUN ERGS-1M**

**D.D. Richardson & R.A. Marshall**

**ABSTRACT**

Comparisons are made between railgun performance predictions made by using the computer code PARA 80, and the experimental data obtained during a series of firings of the ERGS-1M railgun.

It is shown that relatively simple calculations presently give as much insight as detailed computer codes. This is expected to remain so until rigorous determinations of inductance per unit length of railgun rails have been obtained. We recommend that railgun simulation codes and plasma armature codes be developed separately until much greater understanding of railgun behaviour is available.

**Approved for Public Release**

---

**POSTAL ADDRESS: Director, Materials Research Laboratories  
P.O. Box 80, Ascot Vale, Victoria 3032, Australia**

---

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

DOCUMENT CONTROL DATA SHEET

REPORT NO.  
MRL-R-900

AR NO.  
AR-003-793

REPORT SECURITY CLASSIFICATION  
UNCLASSIFIED

TITLE

USE OF THE COMPUTER PROGRAM PARA 80 TO STUDY RESULTS  
FROM FIRING THE RAILGUN ERGS-1M

AUTHOR(S)

RICHARDSON, D.D. & MARSHALL, R.A.

CORPORATE AUTHOR

Materials Research Laboratories  
P.O. Box 50,  
Ascot Vale, Victoria 3032

REPORT DATE  
AUGUST, 1983

TASK NO.  
DST 82/212

SPONSOR  
DSTO

CLASSIFICATION/LIMITATION REVIEW DATE

CLASSIFICATION/RELEASE AUTHORITY  
Superintendent, MRL Physical  
Chemistry Division

SECONDARY DISTRIBUTION

Approved for Public Release

ANNOUNCEMENT

Announcement of this report is unlimited

KEYWORDS

Electric Guns  
Rail-gun simulation Code

COSATI GROUPS

1906

ABSTRACT

Comparisons are made between railgun performance predictions made by using the computer code PARA 80, and the experimental data obtained during a series of firings of the ERGS-1M railgun.

It is shown that relatively simple calculations presently give as much insight as detailed computer codes. This is expected to remain so until rigorous determinations of inductance per unit length of railgun rails have been obtained. We recommend that railgun simulation codes and plasma armature codes be developed separately until much greater understanding of railgun behaviour is available.

SECURITY CLASSIFICATION OF THIS PAGE  
UNCLASSIFIED

# C O N T E N T S

	<u>Page No.</u>
1. INTRODUCTION	1
2. CHANGES NEEDED TO RUN PARA80 ON VAX 11/780	2
3. RESULTS	3
4. DISCUSSION OF THE USE AND VALIDITY OF PARA 80	4
5. SIMULATED PERFORMANCE OF AN ERGS FIRING USING A HP 65 PROGRAMABLE CALCULATOR	5
6. THE CRITICAL IMPORTANCE OF RAIL INDUCTANCE	7
7. CONCLUSIONS	8
8. ACKNOWLEDGEMENTS	9
9. REFERENCES	10

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A-1	



USE OF THE COMPUTER PROGRAM PARA 80 TO STUDY  
RESULTS FROM FIRING THE RAILGUN ERGS-1M

1. INTRODUCTION

This paper describes simulation calculations of railgun performance using the computer code PARA 80 designed by Y.C. Thio [1]. The calculations are used to study the effectiveness of PARA 80 in simulating actual railgun results obtained from a series of firings of the ERGS-1M railgun. The program was originally used to design ERGS-1M, so the performance of the latter compared to the predictions is of much interest.

PARA 80 is a computer program written in FORTRAN which describes the entire railgun circuit. The most important aspect of the program is its description of the plasma armature. This is done with a one-dimensional model, described in some detail in ref. 1.

The hierarchy of subroutines for PARA 80 is shown in Fig. 1. Table I gives a brief explanation of the purpose of each subroutine. The calculation may be considered as divided into two parts. In the first part capacitor discharge dominates and in the second part the capacitor bank has been eliminated from the circuit and inductance dominates. Consider the railgun circuit diagram shown in Fig. 2. The capacitor bank C is initially charged to a nominated voltage. The main switch S<sub>1</sub> is then closed and the simulation begins at this point. When the voltage on the capacitor bank drops below a specified value, the crow-bar switch S<sub>2</sub> is closed, isolating the capacitors from the rest of the circuit. The simulation then switches to an inductively driven mode, the energy of the circuit being taken as now stored in inductor L. The program ceases calculation when the circuit current reduces to a specified value. (Other conditions on termination and crow-bar switching are allowed by the program). The calculation effectively progresses down the barrel from the plasma initiation point in discrete (input) timesteps. The distance it travels down the barrel is determined by the projectile motion and termination condition, and may vary under different simulation conditions.

The experimental railgun ERGS-1M is a small bore (6 x 8 mm) gun with Cu-0.6% Cd rails of length approximately 900 mm [2]. The insulation between the rails is a vulcanised cellulose fibre and the barrel casing is made of Micarta, a high-density glass reinforced resin material. A sketch of the gun is shown in Fig. 3, full specifications are given in Ref. 2.

Instrumentation of firing on ERGS-1M involved recording breach and muzzle voltages, circuit current (with a Rogowski belt) and projectile velocity, in the barrel using inductance coils and outside the barrel using a ballistic pendulum.

This paper reports calculations using PARA 80 to compare with a series of firings of ERGS-1M for initial capacitor voltages between 3.0 and 7.0 kV. The simulation program was run on a VAX 11/780 computer; Ref. 1 described the program structure for a DEC System 10 computer.

## 2. CHANGES NEEDED TO RUN PARA 80 ON VAX 11/780

To transfer the program from the DEC 10 to the VAX 11/780 it was necessary to make several changes. In order to make the data file containing the run specifications more legible, it was reformatted. This was done for all data read into the array CONDAT in subroutine SETUP; the nature of the input data is shown in Table II.

In addition, the subroutine used originally to solve the system of equations, NAG library routine DO2ABF has been removed from the library. The NAG routines on the VAX 11/780 are in double precision, and subroutine DO2BAF was found to be a suitable replacement. This required alteration of the arguments of the subroutine, particularly accuracy specification, and use of double precision variables where relevant. The facility for reducing the timestep size in the original program did not appear to be very effective, and was deleted. A check on the timestep size is now done through changing it in the input data. DO2BAF appears in subroutines CAPSEG and INDSEG, where it uses routines CAPAC and INDUCT, respectively. General adjustments to timestep and accuracy parameters were also required to operate PARA 80 on the VAX computer.

A check on the program was made by repeating conditions of a calculation previously made on the DEC 10 and comparing results. Although it was not possible to reproduce the timesteps exactly as before, agreement was sufficiently close to accept the program as working properly on the VAX 11/780. The disparity arises due to the different ways in which the original equation solver DO2ABF and the new one, DO2BAF, work. The former would change the stepsize if it needed to, while the latter left it fixed. This affected, therefore, the positions at which solutions were found along the barrel. As a result, crowbarring was also not possible at exactly the same position as before.



### 3. RESULTS

The experimental firings on the railgun ERGS-1M produced records of breech and muzzle voltage and circuit current as a function of time. Also recorded were projectile positions as a function of time, and from these, one can estimate velocity as a function of time.

PARA 80, on the other hand, produced curves of current, position and velocity versus time directly. Calculations were performed at the experimental capacitor voltages of 3.0, 4.2, 5.0, 6.0, 7.0 kV. For each of these initial conditions, we were therefore able to compare current profiles, but more interestingly position and velocity of the projectile in the gun.

The calculations were repeated twice : For one series we used gun parameters suggested by the author of the PARA program. These are shown in Table III. For the second series, we repeated the calculations using parameters thought by the present authors to be more realistic. These are also shown in Table III.

To effect a comparison we plot projectile displacement versus time for each of the firings. Results for the 3.0 and 7 kV cases are shown in Figs. 4 and 5.

The positions in the case of the "experimental" curve are determined from magnetic probe measurements, Ref. 3. Six probes were placed on top of the barrel and alternate probes connected together. From the measured induced voltages, the positions versus time were found. The accuracy of these measurements is subject to debate since it was found that the voltage characteristic of adjacent connected probes overlapped to some extent. This distorted the shape of the characteristic, and added to the difficulty of interpretation of the time when the plasma passed the probe. Corrections for the difference between plasma position and projectile position have not been made. It was found, however, that the velocity estimated from the probe positions agreed reasonably well with that determined from the ballistic pendulum displacement on projectile impact.

The results of Figs. 4 and 5 suggest that PARA 80 consistently under-predicts the projectile velocity. The same results were found for the 4.2, 5.0 and 6.0 kV simulations as well. In all cases projectile velocity was consistently lower than experiment. Changing the gun and plasma parameters shown in Table III had some effect - generally a further lowering of projectile velocity - but did not dramatically affect this overall conclusion.

#### 4. DISCUSSION OF THE USE AND VALIDITY OF PARA 80

PARA 80 has been used by its author to predict the performance of various firings of railguns; the predicted data on armature volt drop, current, and projectile position as functions of time appeared to agree well with the experimental results [1,4]. The statement is made in the "User Notes" [1] included with PARA 80 that meaningful interpretations of the results obtained by running the code requires the skills of a plasma physicist. It is well known that computer codes tend to be very personal constructions and it would be truer to say, in this case at least, that meaningful interpretations require the skills of the code's author. The User Notes contain such statements as -

PI	Has the value of 1.0. This is a dummy parameter included for compatibility with future versions of PARA.
A3	Dummy parameter, for compatibility with future versions of PARA.
A5,A6	These should have the value 0.45. Included for compatibility with future versions of PARA.
B6	Dummy parameter
B7	Should have the value of $1.0E-9$
B8	Should have the value of $1.0E+2$
C1-C11	Dummy parameters for compatibility with future versions of PARA.
AB	Should have the value of 0.0
DU	Dummy variable.

Educated guesses can be made about the purposes of some of these parameters, but the author's intention about others is not clear. In the case of parameter A6, this is probably the same as  $\gamma_2$  (p.22 of Ref. 1) where it is stated that " $1-\gamma_2$  is the fraction of current lost through arcing ahead of the projectile; normally assume  $\gamma_2 = 1$ ". This is at variance with the statement in the User Notes that a value of 0.45 should be used. In any event, there is no physical reason to assume that some fixed fraction of gun current is likely to pass the projectile.


We believe that there is little merit in combining an armature plasma code with a railgun performance code as has been done in PARA 80, particularly for small calibre railguns. The performance of a railgun is dependent on one plasma parameter only, namely the resistive voltage drop across it (the so-called muzzle voltage). It makes more sense to use two codes, one for railgun performance and another for the plasma. It is known experimentally (and "confirmed" by computation) that muzzle voltage is largely

independent of current for a particular railgun design so to do a complete simulation of a firing, gun system performance would be predicted by assuming a constant value for muzzle voltage to give current as a function of time. Plasma behavior can be simulated using this function, to give in turn a computed value of muzzle voltage as a function of time. If desired, an iteration could then be made for gun performance using this computed muzzle voltage but further iterations are unlikely to be required because of the insensitivity of gun performance (including gun current) to muzzle voltage.

To make realistic design decisions about the parameters required for future railgun systems, simulation codes assuming a constant value for muzzle voltage are adequate. As noted above, experimentally it is found that muzzle voltage is essentially independent of armature current. This was first observed in the Canberra railgun [5] where the value 200 V was seen with armature current ranging from 300 kA down to the low values of tens of kiloamps. The same constancy was observed in the ERGS experiments [4]. Plasma codes may then be used to enable "fine tuning" to be done. As these simpler codes are refined by comparison with experimental results it should become possible to construct more comprehensive and accurate codes which could be used to calculate the performance of large calibre railgun systems. Large systems will be much too expensive to construct without having very advanced simulations on which to base the designs.

##### 5. SIMULATED PERFORMANCE OF AN ERGS FIRING USING A HP 65 PROGRAMMABLE CALCULATOR

To demonstrate the adequacy of simple simulations for small calibre railguns we include the following model which can be programmed onto a small calculator. The circuit of the ERGS system is as follows -



where\*

m is the railgun projectile mass,  
v is the projectile velocity  
a is the projectile acceleration,  
MV is rail-to-rail voltage across the armature (muzzle volts),  
x is the distance the projectile armature has travelled,  
L' is the inductance per unit length of the railgun rails,  
R' is the resistance per unit length of the railgun rails,  
R is the resistance of the inductor and its leads,  
L is the inductance of the inductor,  
C is the capacitance of the energy storage capacitor,  
V is the voltage produced by the capacitor,  
T is the voltage drop across the main switch when it is conducting,  
S similarly, is the voltage drop across the crowbar switch,  
I is the current flowing in the railgun circuit,  
 $\dot{I}$  is the time rate of change of the current,

and also

t is the elapsed time,  
 $\delta t$  is the time increment used in the simulations.

The equations (in iterative form) which describe the performance of the system are

$$-\dot{I} = ((R + R'x + L'v)I + (MV + T - V))/(L + L'x) \quad (1)$$

$$I = I + \dot{I}\delta t \quad (2)$$

$$a = L'I^2/2m \quad (3)$$

---

\* S.I. units are used throughout.

$$v = v + a\delta t \quad (4)$$

$$x = x + v\delta t \quad (5)$$

$$t = t + \delta t \quad (6)$$

$$V = V - I\delta t/C \quad (7)$$

After the capacitor is crowbarred,  $(MV + T - V)$  in equation (1) is replaced by  $(MV + T + S)$ , and equation (7) is removed.

Simulations of the ERGS shot MIC9 (ref. 3) have been made with the following parameter values

$$C = 0.00614 \text{ F}$$

$$L = 6.8 \text{ E-6 H}$$

$$R = 0.011 \Omega$$

$$MV = 180 \text{ V}$$

$$T = S = 200 \text{ V}$$

$$m = 0.0003 \text{ kg}$$

$$R' = 0.003 \Omega$$

$$V_{\text{initial}} = 7000 \text{ V}$$

Crowbarring was assumed to occur when  $V = -500$ . The results of the two simulations with  $L' = 0.25 \text{ E-6}$  and  $L' = 0.15 \text{ E-6}$  are plotted in Fig. 5.

## 6. THE CRITICAL IMPORTANCE OF RAIL INDUCTANCE

It can be seen that the simulation performed with the lower value of  $L'$  matches the experimental data well. This value of  $0.15 \mu\text{H/m}$  is very low. The value for  $L'$  obtained in the same way for the Canberra railgun [5] is  $0.42 \mu\text{H/m}$ .

We believe that the difference between actual performance and measured performance has much to do with frictional drag on the projectile as it is being accelerated in the railgun. Lower values of  $L'$  indicate higher friction. Higher friction effects are to be expected in smaller guns and this is what the results show. The ERGS railgun has a bore size of  $6 \text{ mm} \times 8 \text{ mm}$  compared with the Canberra railgun bore of  $12.7 \text{ mm}$  square.

It can be argued that the selection of some particular value of  $L'$  to make a simulation match measured performance is a questionable procedure. The author of PARA 80 had a similar factor that he adjusted to get agreement, namely  $\gamma$ . The question then arises, how should the unknown factors be handled? The answer to this is, "In the manner which gives the greatest insight". Perhaps then we should be simulating by using a computed value of  $L'$  in equation (1) and modifying the acceleration equation (3) to read

$$a = (0.5 L' I^2 - F)/m$$

where  $F$  is the friction force. If friction force is proportional to the driving force, then the effect will be the same as using a modified value for  $L'$ .

It should be noted that, in any case, the area of greatest uncertainty in the simulation of railgun systems is the value to take for  $L'$ , the rail inductance per unit length. Depending on the assumptions made, values can vary greatly. The three main possibilities are:

- (1) current density uniform within the rails,
- (2) current confined to the inner surface of the rails to the full rail height, and
- (3) current confined to inner rail surface, the sheet width being equal to the bore height.

For the Canberra railgun these computed values [5,6,7] are 0.503, 0.493 and 0.628  $\mu\text{H/m}$ . For ERGS, the respective values are 0.557, 0.552 and 0.732  $\mu\text{H/m}$ .

Work recently reported gives hope that realistic computed values for  $L'$  will be available soon [8,9,10].

## 7. CONCLUSIONS

Fig. 5 contains two curves estimated by using a simple model of the railgun. With an empirically determined value of the rail inductance of  $L' = 0.15 \mu\text{H/m}$ , good agreement is found with experiment. Use of eqn 4.16 of ref. 1 indicates a value of  $L' = 0.8 \mu\text{H/m}$ , which is considerably larger. In PARA 80, it is thought that  $\gamma$  of eqn 4.16 [1] is input rather than calculated. In this case, a value of  $\gamma = 0.45$  as recommended in the "User Notes" is much higher than the value of 0.24 obtained from Ref. 1 eqn (4.17).

Difficulties in interpreting the meaning of various aspects of PARA 80, such as this, considerably limit the usefulness of the program for

the present work. The program is written in a convoluted manner, and uses unusual scaling of variables, both of which make it very difficult to understand from the source listing. The possibilities of modifying or improving aspects of the code are therefore limited.

We believe that for small calibre railguns quite simple simulation codes can be used to compute performance. Using such codes and experiments it will be possible to determine the critical physical parameters needed to construct more comprehensive codes. Large codes will be needed for design and analysis of large calibre railguns. At present a critical area in need of resolution is the value of inductance per unit length of rails in railguns and this is being addressed.

#### 8. ACKNOWLEDGEMENTS

The authors acknowledge the assistance of Mr G.A. Clark and Drs A.J. Bedford and V. Kowalenko in the preparation of this report. External support from the US DARPA for the EML program at MRL is gratefully acknowledged.

## 9. REFERENCES

1. Thio, Y.C., (a) "PARA : A Computer Simulation Code for Plasma Driven Electromagnetic Launchers", MRL Report MRL-R-873 (1983).  
(b) "PARA Release Version 1.0 User Notes : May 1982" (Distributed with the FORTRAN version of PARA to US and Australian Users).
2. Bedford, A.J., Clark, G.A. and Thio, Y.C. "Experimental Electromagnetic launchers at MRL", MRL Report MRL-R-894 (1983).
3. Clark, G.A. and Bedford, A.J. "Electromagnetic Launcher Performance Results of a Small Calibre Launcher", MRL Report (1983), In preparation.
4. Thio, Y.C., Clark, G.A. and Bedford, A.J. "Results from an experimental railgun system : ERGS-1A". MRL-R-875 (1983).
5. Rashleigh, S.C. and Marshall, R.A. "Electromagnetic acceleration of macroparticles to high velocities", J. Appl. Phys. 49(4) April 1978, pp.2540-2542.
6. Rosa, B. and Grover, F.W. "Bulletin of the Bureau of Standards" 8 (1) (1912).
7. Grover, F.W. "Inductance Calculations", Dover Publications (1962).
8. Kerrisk, J.F. "Electrical and Thermal Modeling of Railguns". 2nd Symposium of EML Technology, Boston MA, Oct 1983.
9. Holland, L.D. "The DES Railgun Facility at CEM-UT". 2nd Symposium of EML Technology, Boston MA, Oct 1983.
10. Marshall, R.A. "Current Flow Patterns in Railgun Rails". 2nd Symposium of EML Technology, Boston MA, Oct 1983.



TABLE I

PURPOSES OF PARA 80 SUBROUTINES

PAMPS (MAIN)	-	General control, files opened and closed.
SETUP	-	Reads input data, defines constants and constructs scaled quantities.
NORMAL	-	Normalises input data according to the scales from SETUP.
EXTRAC	-	Structures the array GUNDAT for the actual calculation.
SGUN	-	Controls simulation of the railgun itself.
INTERP	-	Interprets the data stored in GUNDAT.
CAPSEG	-	Controls the simulation of the capacitively driven gun.
INDSEG	-	Controls the simulation of the inductively driven gun.
RESULT	-	Prepares data for output, calculates physical properties and outputs results.
DO2BAF	-	Solves (in double precision) a system of ordinary differential equations.
PHYCON	-	Calculates pressure behind projectile with radiation and magnetic terms only.
MAGCON	-	As for PHYCON but includes gas pressure term as well (for closed breech simulation).
CAPAC	-	Calculates the integrand for DO2BAF for the capacitively driven gun - i.e. finds the array F(10).
INDUCT	-	As CAPAC but for the inductively driven gun.
PLASMA	-	Calculates armature plasma properties.
VETROD	-	Gives electrode potential.
VRIAL	-	Calculates potential drop along the rails.

# TABLE II

## THE NATURE OF PARAMETERS INPUT TO PARA 80

<u>PARA data meanings</u>	<u>Typical</u>
<u>Line 1:</u> Type of foil	ALUMINIUM
<u>Line 2:</u>	
Ionisation potential of plasma ions (eV)	5.98
Atomic weight of plasma ions	26.98
Density of foil kg m <sup>-3</sup>	2.7 E3
Height of foil )	6.0E-3
Width of foil ) metres	44.0E-3
Thickness of foil )	15.0E-6
<u>Line 3:</u> CONDAT (n,1)	
n	
1 If > 0.5 entirely inductive simulation	0.0
2 Reference voltage for scaling (Volts)	10.0E+3
3 Reference capacitance (Farads)	4.E-3
4 Another dummy parameter (May be used in the NAG file routine?)	0.5E-6
5 Projectile mass (kg)	.31E-3
6 $\gamma_1 = 0.45$	0.45
7 $\gamma_2 = 0.45$ half of fraction of current not lost through arcing	0.45
8 Separation between the rails (m)	8.E-3
9 Height of the bore (m)	6.0E-3
10 Rail height (m)	10.E-3

Line 3 (contd)	Typical
11-20 Not used - set to zero	0.0

Line 4:

n		
1	If > 0.5 skips normalisation (in NORMAL) (Unit indicator) Indicates whether the quantities are in the same line	0.0
2	Electrode potential drop per electrode (Volts)	10.0
3	Magnetic permeability of the medium ( $Hm^{-1}$ )	1.257E-6
4	Resistivity of rail material ( $\Omega m$ )	2.E-8
5	Height of the bore (m)	6.E-3
6	Resistivity of armature ( $\Omega m$ ) (Dummy parameter)	4.E-8
7	Width of the bore (m)	8.E-3
8	Value $1.0 \times 10^{-9}$ ) These are presumably more	1.E-9
9	Value $1.0 \times 10^{-2}$ ) dummy parameters	0.5E+2
10	Resistivity of bus-bar material ( $\Omega m$ )	2.7E-8
11	Length to width ratio of bus-bar	160
12	Resistance of the circuit other than bus-bar, rails & plasma ( $\Omega$ )	10.9E-3
13-20	Not used - set to zero	0.0

Line 5: CONDAT (n,3)

n		
1	)	
2	)	
3	)	
4	) Not used - all set to zero	0.0
5	)	
6	)	
7	)	

Typical

Line 6: CONDAT (n,4)

n

1	Number of segments (should be 1.0) (NSEG)	1.0
2	0.0 for results in physical (SI) units, 1.0 for normalized units	0.0
3	Relative error of computed results	1.E-9
4	No. of timesteps skipped before computed results output to files	1.0

Line 7:

n

1	Unknown	0.0
2	Unknown	0.0
3	Inductance of storage inductor and stray inductance, excluding rail inductance (H)	6.6E-6
4	Capacitance of capacitor bank (F)	6.14E-3
5	Initial position of projectile relative to closed breech (m)	5.E-2
6	Initial current (usually zero) (A)	0.0
7	Initial velocity of projectile (kms <sup>-1</sup> )	0.0
8	Initial capacitor voltage (V)	3.E+3
9	Initial value of time (usually zero) (sec)	0.0
10	Time step of simulation (sec) (TINTLO, TINTVL)	1.3E-5
11	CONTYP - Controls which condition is used for crow-bar and termination (ICON)	8.0
12	CONVAR - Criterion to control crow-barring and final termination	-500

	Typical
Line 7: (contd)	
13    CONSUP - termination control + Simulation terminates after the current has fallen below a given fraction of the current at the contact of crow-bar	0.8
14    Initial Plasma temperature (K)	2.6E+3
15    ABSORB (zero), meaning unclear	0.0
16-20 Not used - set to zero	0.0
Line 8:    CONDAT (n,6)	
n	
1    Unknown	0.0
2    Unknown	0.0
3-15 No. of simulations required on varying the relevant (n,5) parameter	1.0
16-20 Not used - set to zero	0.0
Line 9:    CONDAT (n,7)	
n	
1    Unknown	0.0
2    Unknown	0.0
3-15 Increments of parameters (n,5) if relevant, (n,6)>1.0 [(n,5) gives starting value].	not used
16-20 Not used - set to zero	0.0

T A B L E III

CHANGES TO INPUT PARAMETERS FOR PARA 80 BETWEEN THE  
ORIGINAL AUTHOR AND THE PRESENT AUTHORS' ESTIMATES

CONDAT PARAMETER	SIGNIFICANCE	ORIGINAL	NEW*
(2,2)	Electrode potential drop	60 V	10 V
(4,2)	Resistivity of rail material	$4 \times 10^{-8} \Omega m$	$2 \times 10^{-8} \Omega m$
(10,2)	Resistivity of busbar material	$4 \times 10^{-8} \Omega m$	$2.7 \times 10^{-8} \Omega m$
(12,2)	Resistance of circuit ex busbar, rails, plasma	0.005 $\Omega$	0.0109 $\Omega$

\* Prepared with the advice of Dr V. Kowalenko




FIG. 1 Hierarchy of subroutines used in PARA 80





FIG. 2 Circuit diagram of the ERGS-1M experiment





ERGS-1M BARREL AND BREECH ASSEMBLY

FIG. 3 Sketch of the ERGS-1M railgun




FIG. 4 Plots of position vs time for initial capacitor voltage of 3.02 kV. (a) Results of the author of PARA 80, (b) Results for the "improved" parameters shown in Table III, (c) Results as for (a) except for a foil mass of 0.036 gm (compared to 0.0104 gm for (a) or (b)). (d) Experimental (MIC 11). Ballistic pendulum measurements give  $1500 \text{ ms}^{-1}$  as the final velocity. Rough estimates from the curves give the following velocities near the end of the barrel:

- (a)  $800 \text{ ms}^{-1}$
- (b)  $750 \text{ ms}^{-1}$
- (c)  $1225 \text{ ms}^{-1}$
- (d)  $1500 \text{ ms}^{-1}$




FIG. 5 As for Fig. 4 but at an initial capacitor voltage of 7 kV.  
Velocity estimates are:

Ballistic Pendulum  $3300 \text{ ms}^{-1}$  (MIC 2)

- (a)  $1875 \text{ ms}^{-1}$
- (b)  $1450 \text{ ms}^{-1}$
- (c)  $2050 \text{ ms}^{-1}$
- (d)  $3200 \text{ ms}^{-1}$

Curves (e) and (f) are calculated from the simple model  
given in the paper for (e)  $L' = 0.25 \mu\text{H/m}$ ,  
(f)  $L' = 0.15 \mu\text{H/m}$ .

(MRL-R-900)

DISTRIBUTION LIST

MATERIALS RESEARCH LABORATORIES

Director  
Superintendent, Physical Chemistry Division  
Dr A. Bedford  
Dr J. Eadie  
Library (2 copies)  
Dr D.D. Richardson  
Dr R.A. Marshall

DEPARTMENT OF DEFENCE

Chief Defence Scientist/Deputy Chief Defence Scientist/ (1 copy)  
Controller, Projects and Analytical Studies/  
Superintendent, Science and Technology Programme  
Army Scientific Adviser  
Air Force Scientific Adviser  
Navy Scientific Adviser  
Officer-in-Charge, Document Exchange Centre (17 copies)  
Technical Reports Centre, Defence Central Library  
Central Office, Directorate of Quality Assurance - Air Force  
Deputy Director, Scientific and Technical Intelligence,  
Joint Intelligence Organisation  
Librarian, Bridges Library  
Librarian, Engineering Development Establishment  
Defence Science Representative, (Summary Sheets Only)  
Australia High Commission, London  
Counsellor, Defence Science, Washington, D.C. (Summary Sheets Only)  
Librarian, (Through Officer-in-Charge), Materials Testing  
Laboratories, Alexandria, NSW  
Senior Librarian, Aeronautical Research Laboratories  
Senior Librarian, Defence Research Centre, Salisbury, SA

DEPARTMENT OF DEFENCE SUPPORT

Deputy Secretary, DDS  
Head of Staff, British Defence Research & Supply Staff (Aust.)

OTHER FEDERAL AND STATE DEPARTMENTS AND INSTRUMENTALITIES

NASA Canberra Office, Woden, ACT  
The Chief Librarian, Central Library, CSIRO  
Library, Australian Atomic Energy Commission Research Establishment

MISCELLANEOUS - AUSTRALIA

Librarian, State Library of NSW, Sydney, NSW  
University of Tasmania, Morris Miller Lib., Hobart, Tas.

(MRL-R-900)

DISTRIBUTION LIST  
(Continued)

MISCELLANEOUS

Library - Exchange Desk, National Bureau of Standards, USA  
UK/USA/CAN/NZ ABCA Armes Standardisation Representative (3 copies)

[REDACTED]  
[REDACTED]  
Director, Defence Research Centre, Kuala Lumpur, Malaysia  
Exchange Section, British Library, UK  
Periodicals Recording Section, Science Reference Library,  
British Library, UK  
Library, Chemical Abstracts Service  
INSPEC: Acquisition Section, Institute of Electrical Engineers, UK  
Engineering Societies Library, USA  
Aeromedical Library, Brooks Air Force Base, Texas, USA  
Ann Germany Documents Librarian, The Centre for Research  
Libraries, Chicago, Ill.  
Defense Attache, Australian Embassy, Bangkok, Thailand  
(Att. D. Pender)

ADDITIONAL DISTRIBUTION

DARPA/TTO, 1400 Wilson Boulevard, Arlington, VA 22209, USA  
(Attn. Dr H.D. Fair Jr)  
ARRADOM, Dover, NJ 07801, USA, Building 382  
(Attn. Dr P.J. Kemney, Dr T. Gora)  
ARRADCOM, Ballistics Research Laboratory DRDAR-BLB, Aberdeen  
Proving Ground MD 21005, USA  
(Attn. Dr D. Eccleshall, Dr J.D. Powell)  
Naval Surface Weapons Centre (NSWC/DL), Dahlgren, VA 22448, USA  
(Attn. Dr M.F. Rose Code F-04, Dr H.D. Odom Code F-12)  
Naval Research Laboratory, Code 4770, Washington DC 20375, USA  
(Attn. Dr R. Ford, Dr I. Vitkovitsky)  
US Air Force, Armament Laboratory (AFATL/DLDB),  
Eglin Air Force Base FL 32542, USA  
(Attn. Dr L. Burge, Dr W. Lucas, Lt R. Walley)  
US Air Force, Aero Propulsion Laboratory, Power Division (AFWAL/POOS-2)  
Wright-Patterson Air Force Base OH 45433, USA  
(Attn. Dr C. Oberly)  
US Air Force, Office of Scientific Research, Bolling AFB,  
Washington DC 20332, USA (Attn. Dr L. Caveny)  
US Air Force, Rocket Propulsion Laboratory, Edwards AFB,  
CA 93523 (Attn. LKDH/Lt Phil Roberts)  
NASA Ames Research Centre, Moffet Field CA 94035, USA  
(Attn. Technical Library)  
NASA Langley Research Center, Langley Field Station, Hampton VA 23365,  
USA (Att. Technical Library)  
NASA Lewis Research Center, Cleveland OH 44135, USA  
(Attn. William R. Kerslake)

(MRL-R-900)

DISTRIBUTION LIST  
(Continued)

ADDITIONAL DISTRIBUTION (Contd)

NASA Goddard Space Flight Centre, Greenbelt MD 20771, USA  
(Attn. Technical Library)  
NASA Scientific and Technical Information Facility,  
Baltimore MD 21240, USA  
(Attn. Accessioning Department)  
Jet Propulsion Laboratory, 4800 Oak Grove Drive, Pasadena CA 91102  
USA (Attn. Technical Library)  
Batelle Columbus Laboratories, 505 King Avenue, Columbus OHIO 43201  
USA (Attn. Dr Eric Rice)  
General Dynamics, Kearney Mesa Plant, P.O. Box 1128, San Diego  
CA 92112, USA (Attn. Dr J.H. Cuadros (Pomona Division))  
International Applied Physics, Research, 7546 McEwen Road,  
Dayton OHIO 45459, USA (Attn. Dr J.P. Barber)  
Lawrence Livermore National Laboratories, PO Box 808,  
Livermore, CA 94550, USA (Attn. Dr Ron Hawke)  
Litton Industries, 360 North Crescent Drive, Beverly Hills CA 90210  
USA (Attn. Dr R. Salter, Dr J. Scudder)  
Los Alamos National Laboratory, Mail Stop 525, Los Alamos NM 87545,  
USA (Attn. Dr. Jerry Parker)  
Los Alamos National Laboratory, Mail Stop 985, Los Alamos NM 87545,  
USA (Attn. Dennis Peterson)  
Massachusetts Institute of Technology, Francis Bitter National  
Magnet Laboratory, Cambridge MA 02139, USA  
(Attn. Dr H. Kolm)  
Physics International Company, 2700 Merced Street, San Leandro  
CA 94577, USA (Attn. Dr Ed Goldman)  
Science Applications Inc. 6600 Powers Ferry Road (Suite 220),  
Atlanta GA 30339, USA (Attn. Dr J.H. Batteh)  
University of Texas at Austin, Center for Electromechanics (CEM),  
Austin TX 78712, USA (Attn. Dr William Weldon)  
Vought Corporation, Advanced Technology Center, PO Box 226144,  
Dallas, TX 75266, USA (Attn. Dr C.H. Haight, Dr Mike Tower)  
Westinghouse Electric Corporation, 1310 Baulah Road,  
Pittsburgh PA 15235, USA  
(Attn. Mr C.J. Mole, Dr I. McNab, Dr D.W. Dais, Dr Y.C. Thio)  
Westinghouse Electric Corporation, Sunnyvale CA 94088, USA  
(Attn. Mr William A. Volz)  
Sandia Laboratories, Albuquerque, NM 87115, USA  
(Attn. Dr M. Cowan)  
Rand Corporation, Santa Monica, CA, USA  
(Attn. Dr. Gerald A. Sears, Dr William J. Whelan)  
General Atomics, San Diego CA, USA (Attn. Dr Sibley Burnett)  
JAYCOR, 205 South Whiting Street, Alexandria VA 22304, USA  
(Attn. Dr Derek Tidman)  
General Electric Company, Schenectady NY, USA  
(Attn. Mr Robert A. Marshall)  
Research School of Physical Sciences, Australian National  
University, Box 4 PO, Canberra, ACT 2601  
(Attn. Prof. S. Kaneff)

END

DATE  
FILMED

4 84

DT